

BEFORE



AFTER



BRICK FILLER

TEXTURED BRICK REPAIR FILLER

The ultimate solution for flawless brick repairs. Specially formulated for both interior and exterior applications.

This pre-mixed and pre-coloured brick repair filler combines convenience with exceptional quality to deliver repairs of a professional standard.

The textured, hand-blended, formula looks and feels like natural brick for virtually invisible repairs.

Benefits

NATURAL TEXTURED BRICK FINISH

Our Brick Filler features a textured formulation that mimics the appearance of natural brick. It seamlessly blends with your existing brickwork, ensuring a repair that is virtually invisible.

REPAIR CHIPS, CRACKS, DRILL HOLES & MORE

From minor chips and cracks to drill holes and other damage, our Brick Filler is the go-to solution. Effortlessly tackle a wide range of repairs while restoring the integrity and beauty of brick surfaces.

SEAMLESS COLOUR MATCHING

Seamlessly blend repairs into the existing brickwork by choosing from a selection of 12 popular brick shades, carefully curated to match popular UK brick shades. Want a different colour? No problem, simply blend colours together, or enhance shade precision with our compatible Stonelux Pigments.

READY TO USE

Ready to use straight out of the tub. Dive straight into your project without the need for careful mixing, saving valuable time and effort.

PROFESSIONAL QUALITY RESULTS

No matter your skill level, our Brick Filler enables you to achieve professional-quality repairs.





Visit Us Online

- Order Now
- View Colours
- Downloads

Application

PREPARATION

Remove any loose material using a wire brush. Ensure the damaged brick is clean, sound and dry. Apply a suitable stabiliser if the brick is unsound.

REPAIR METHOD

1. Firmly press the filler into the damaged area using a small pointing trowel or similar. Reform the brick face level with surrounding bricks.
2. Reshape the surface of the repair to match the form and contours of the original brick.
3. If the damage is deeper than 12mm, build the repair in layers no thicker than 12mm. Leave each layer at least 12 hours to dry.

Technical Information

Use On	Bricks, stone, and mortar. Ideal for chips, cracks, drill holes, spalling and other damage.
Environment	Interior & Exterior
Coverage	Standard size brick (201mm x 65mm) approximately 1½ brick faces at 12mm deep.
Drying Time	Leave a minimum of 12 hours between layers. Shower proof in 12 hours, fully cured in 7 days. Drying time is dependant upon ambient conditions.
Colours	12 common brick colours. Bespoke colours and colour-matching also available (min. order quantity applies).
Texture Level	Textured
Composition	Water-based
Cleaning	To clean tools, remove as much material as possible from tools before cleaning with water.
Available Sizes	300g, 700g, 1.4kg, 3.5kg
Limitations	Do not apply in rain, temperature below 10°C or above 30°C or if exposure to these is likely during the curing time. Do not use below DPC level.



1. BEFORE



2. AFTER

1. BEFORE : Damage to a brick face caused by spalling.
2. AFTER: Brick face repaired using Stonelux Brick Filler contoured to match surrounding bricks.