



BRICK TINT

FOR STONE, BRICK & MORTAR

A premium grade, professional brick tint designed to enhance the natural beauty of porous masonry surfaces such as brick, stone and mortar.

It offers exceptional colour modification possibilities while effectively permeating the substrate's pores, resulting in both a stunning and long-lasting finish that lasts the test of time.



Benefits

SEAMLESS COLOUR CORRECTIONS

Effectively conceal repairs and colour corrections by blending flawlessly with existing brickwork.

EFFORTLESS RESTORATION

Our Stonelux Brick Tint simplifies the restoration process, allowing you to effortlessly revive and enhance the appearance of unsightly masonry.

TIME AND COST SAVINGS

Save time and money by avoiding the need for expensive brick replacements. Restore the beauty of masonry without the hassle or expense of extensive renovations.

DEEP PENETRATION & LONG LASTING RESULTS

Our advanced formula ensures deep penetration into the pores of the brick or stone surface, resulting in a permanent stain that does not alter the natural make up of the substrate.

HARD WEARING WITH ZERO MAINTENANCE

Stonelux Brick Tin's colour fastness and durability ensures that your efforts are a permanent and will continue to look stunning for years to come. No need for touch ups or maintenance.

Technical Information

Range of Use	Bricks, stone and mortar. Do not use on non-porous surfaces. (for non-porous bricks please use Stonelux Brick Coating).
Environment	Interior & Exterior
Coverage	10 - 12.5 m ² per 1 Litre. Coverage will vary by substrate, porosity and desired effect.
Drying Time	2 - 3 hours (dependant upon ambient conditions).
Colours	12 common brick colours. Bespoke colours and colour-matching also available.
Finish	Permanent
Gloss Level	Matt
Available Sizes	75ml sample, 1 litre, 2.5 litre, 5 litre.
Limitations	Not suitable for non-porous surfaces. Do not apply in rain, temperatures below 10°C, above 30°C or if exposure to these conditions is likely during drying time. Store in a dry area away from direct sunlight. Store between 5°C and 25°C.



Visit Us Online

- Order Now
- View Colours
- Downloads

Application

METHOD

Brush

PREPARATION

Ensure surface is clean, sound and dry.

APPLICATION INSTRUCTIONS

Mix/shake well before use. Apply using a brush (we recommend 2" for most bricks and 0.5" for mortar joints). Additional coats can be applied for a darker shade. A lighter finish can be achieved by diluting with water to a maximum 50:50 ratio. Overlapping brush strokes can result in shade variations.

TIPS

- Test colour on a discrete area and allow to thoroughly dry.
- Drain excess tint from brush before applying to brick to keep drips to a minimum.
- Tint bricks in a random pattern rather than row by row to avoid a light to dark effect across the row.
- Keep some clean water to hand to quickly clean up any spills.



1. BEFORE - Mis-coloured and stained brickwork.
2. AFTER - Colour corrected with Stonelux Brick Tint in Medium Red.